## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: ALCO							
Supplier's address: Einkauf, Hilsmannweg 9, 59755 Arnsberg, DE							
Model identifier: 9080-2- / 9085-10							
Type of light so	urce:						
Lighting technol	logy used:	LED	Non-directional or directional:	-			
Light source cap (or other electri Mains or non-m	ic interface)	EDISON SMD 2835 MLS	Connected light source (CLS):	Ja			
Colour-tuneable	e light source:	Nein	Envelope:	-			
High luminance	light source:	Nein					
Anti-glare shield	d:	Nein	Dimmable:	Yes			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		72	Energy efficiency class	D			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		- in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	_			
On-mode power (P <sub>on</sub> ), expressed in W		80,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer dimensions without	Height	1 950	Spectral power	See image			
	Width	280	distribution in the	in last page			
	Depth	610		Seite 1 / 2			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		<del>-</del>	If yes, equivalent power (W)	-		
			Chromaticity	-		
			coordinates (x and y)	-		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		10	Survival factor	-		
the lumen maintenance factor		-				
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)		-	Colour consistency in McAdam ellipses	3		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		Ja <sup>(b)</sup>	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)		<del>-</del>	Stroboscopic effect metric (SVM)	-		

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;